



Unit : mm

Model	Tube φD.	R	A	B	L	φP	C	E	Hex. H	Weight (g)	Orifice dia. (φmm)	Eff. sect. Area (mm ²)	CAD file No.
PPB4-M5SUS□□	4	M5×0.8	2.9	20.3	22.4	10	14.9	16.9	10	9	1.8	1.5	TFPP-013
PPB4-01SUS□□		R1/8	8	23.3	24.3					12	4.1		
PPB4-02SUS□□		R1/4	11	26.3	25.3					14	20.5		
PPB6-M5SUS□□	6	M5×0.8	2.9	23	25.6	13	17	20.2	12	14	1.8	1.5	
PPB6-01SUS□□		R1/8	8	26	28.5					15.5	10		
PPB6-02SUS□□		R1/4	11	29	29.5					14	23		
PPB8-01SUS□□	8	R1/8	8	26.5	30	15	18.4	22.4	14	19.5	6	16.5	
PPB8-02SUS□□		R1/4	11	29.5	31					25			
PPB10-02SUS□□	10	R1/4	11	36	38.8	17.5	20.2	25.2	17	36.5	8	30	
PPB10-03SUS□□		R3/8	12	37	39.5					44			
PPB12-03SUS□□	12	R3/8	12	39	43.2	21	22.9	28.4	21	54.5	10	47	
PPB12-04SUS□□		R1/2	15	42	44.3					69			

*1. L dimension is a reference dimension after tightening screw.

*2. Please enter C in the □ of model code only when Clean room specification is required.

*3. Please enter S in the □ of model code when Sealock™ treated on screw is required.