


PPC

Straight

Screw material SUS304



Unit : mm

Model	Tube φD.	R	A	B	L	C	Hex. H	Weight (g)	Orifice dia. (φmm)	Eff. sect. Area (mm ²)	CAD file No.
PPC4-M5SUS□□	4	M5×0.8	2.9	20	17.1	14.9	10	6	1.8	1.9	TFPP-011
PPC4-01SUS□□		R1/8	8	21	17			8	3	5.3	
PPC4-02SUS□□		R1/4	11		15		14	15			
PPC6-M5SUS□□	6	M5×0.8	2.9	22	19.1	17	12	8.5	1.8	1.9	
PPC6-01SUS□□		R1/8	8	22.6	18.6			14	16	4.6	
PPC6-02SUS□□		R1/4	11	24.6							
PPC8-01SUS□□	8	R1/8	8	27.9	23.9	18.2	14	14.5	6	20	
PPC8-02SUS□□		R1/4	11	26.6	20.6						
PPC10-02SUS□□	10	R1/4	11	29.8	23.8	20.7	17	18.5	8.5	35	
PPC10-03SUS□□		R3/8	12	29.3	22.8						
PPC12-03SUS□□	12	R3/8	12	31.9	25.4	23.3	21	32.5	11	59	
PPC12-04SUS□□		R1/2	15	33.9	25.9						

*1. L dimension is a reference dimension after tightening screw.

*2. Please enter C in the □ of model code only when Clean room specification is required.

*3. Please enter S in the □ of model code when Sealock treated on screw is required.