



Unit : mm

Model	Tube φD.	R	A	B	L	φP	C	E	Hex. H	Weight (g)	Orifice dia. (φmm)	Eff. sect. Area (mm ²)	CAD file No.	
PPD4-M5SUS□□	4	M5×0.8	2.9	20.3	34.3	10	14.9	16.9	10	9	1.8	1.9	TFPP-014	
PPD4-01SUS□□		R1/8	8	23.3	36.3					12		3.8		
PPD4-02SUS□□		R1/4	11	26.3	37.3					14		20.5		3.9
PPD6-M5SUS□□	6	M5×0.8	2.9	24	40.3	13	17	20.3	12	14	1.8	1.9		
PPD6-01SUS□□		R1/8	8	26	42.3					15.5		4.6		12.5
PPD6-02SUS□□		R1/4	11	29	43.3					14				
PPD8-01SUS□□	8	R1/8	8	28.2	46.4	15	18.1	22.2	14	20	6	20		
PPD8-02SUS□□		R1/4	11	31.2	47.4					25.5				
PPD10-02SUS□□	10	R1/4	11	36	55.4	17.5	20.2	25.4	17	36.5	8	35		
PPD10-03SUS□□		R3/8	12	37	56.1					44				
PPD12-03SUS□□	12	R3/8	12	39.2	61.5	21	22.9	28.4	21	54.5	10	59		
PPD12-04SUS□□		R1/2	15	42.2	62.6					69				

*1. L dimension is a reference dimension after tightening screw.

*2. Please enter C in the □ of model code only when Clean room specification is required.

*3. Please enter S in the □ of model code when Sealock treated on screw is required.